

TWO COLOURS



ONE DIRECTION

Polyethylene  
**TIPELIN 6000B**  
Bimodal HDPE for blow moulding

### Description

TIPELIN 6000B is a high density bimodal polyethylene copolymer (with butene-1 as comonomer) intended for blow moulding of products with high stiffness and very good environmental stress crack resistance (ESCR). The grade contains antioxidant and acid scavenger.

### Applications

TIPELIN 6000B is recommended for thin walled, small bottles up to 5 litre capacity for consumer goods such as cosmetics, daily care etc. and for blow moulded products for packaging of aggressive industrial chemicals bounded to UN certificates. It is suitable for corrugated pipes too.

TIPELIN 6000B is suitable for food contact, for manufacturing of pharmaceutical packing products and toys. The product complies with Food Contact, Pharmaceutical and Toy Safety Regulations.

### Properties

	Test method	Unit	Typical value
Melt Mass-Flow Rate (MFR) (190 °C /2.16 kg)	ISO 1133	g/10 min	0,30
Melt Mass-Flow Rate (MFR) (190 °C /5.0 kg)	ISO 1133	g/10 min	1,3
Melt Mass-Flow Rate (MFR) (190 °C /21.6 kg)	ISO 1133	g/10 min	30
Density (23 °C) *	ISO 1183-2	kg/m <sup>3</sup>	958
Tensile Strength at Yield *	ISO 527-3	MPa	32
Tensile Strain at Yield *	ISO 527-3	%	11
Tensile Strain at Break *	ISO 527-3	%	1350
Flexural Modulus *	ISO 178	MPa	1700
IZOD Impact Strength (notched, 23 °C) *	ISO 180/ A	kJ/m <sup>2</sup>	8
Vicat Softening Temperature *	ISO 306/A 120	°C	127
Shore D Hardness *	ISO 868	-	65
ESCR F50 B (10% Igepal CO-630) *	ASTM D 1693	h	200
OIT (200 °C) *	EN 728	min	30

Typical properties, not to be used as specification.

\* Average mechanical property values of several measurements carried out on standard pressed specimens (ISO 293) conditioned at room temperature (ISO 291).

TIPELIN TIPOLEN TIPPLEN TATREN BRALEN

The joint product portfolio of TVK and Slovnaft provide infinite opportunities

MEMBERS OF THE MOL GROUP



## Processing

TIPELIN 6000B can be used in conventional blow moulding machines. Recommended processing temperature 170-190 °C.

## Storage and Handling

Pellets are packed in 25 kg PE-LD bags and transported on stretch-wrapped pallets at load of polymer 1375 kg. Heat treated pallets are available as well. Transportation in a road silo or rail silo is also available. For more detailed information please contact SLOVNAFT a.s. and TVK Plc. sales representative.

Since polyethylene is a combustible substance, the fire safety rules applicable for combustible materials in warehouses and store rooms should be observed.

If polymer is stored in conditions of high humidity and fluctuating temperatures, then atmospheric moisture can condense inside the packing. If it happened, it is recommended the pellets to be dried before use. During the storage polyethylene should not be exposed to UV radiation and temperatures above 40 °C. Producer does not take responsibility for any damages caused by adverse storage.

## REACH Statement

Polymers are exempt of REACH registration. However their raw materials which mean monomers, catalysts and relevant additives have been registered. TVK Plc. and SLOVNAFT a.s. are committed to fully respect legislation and will only use REACH compliant raw materials. At this point in time TIPELIN do not contain any substances specifically identified as SVHC at levels greater than 0.1%.

## Safety

See MSDS.

## Recycling

Polyethylene resins are suitable for recycling using modern recycling methods. In-house production waste should be kept clean to facilitate direct recycling.

## Disclaimer

The information provided in this publication has been compiled to the best of our present knowledge. However, in view of the various applications of polyethylene resins and the equipments used, the processing conditions may differ.

The recommendations and data herein are to be construed as informatory only and do not relieve users from carrying out their own tests and experiments prior to processing in order to check suitability for a specific use. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed. Our products are under continuous development, therefore we reserve the right to change the information presented in this brochure at our own discretion.

The REACH statement herein does not constitute legal advice. The REACH statement is provided for informational purpose only.

TIPELIN TIPOLEN TIPPLEN TATREN BRALEN

The joint product portfolio of TVK and Slovnaft provide infinite opportunities

MEMBERS OF THE MOL GROUP

